



## DTL-319S100

















## DTL-319S100 LCD TV

Aspect Ratio         16 : 10           Pixel Pitch         0.285(H) x 0.285(V)mm           Panel Resolution         1440 x 900           Brightness         300 cd/m2           Contrast Ratio (typ.)         800 : 1           Response Time (typ.)         5 ms           Viewing Angles (typ.)         170°(H) / 160°(V)           Standard TV         B/G, D/K, I, L/L=           Tuner System         PAL, SECAM           Display Color         16.7 M           Control Panel         Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2),           Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel           IR Receiver           Terminal I/O         SCART x 2, TV Tuner, S-Video, CVBS, D-Sub           Support Timing         480i, 480p, 576i, 576p           User Controls         Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)           Pic-Mode         Personal / Native / Soft / Bright           Sleep Timer Function         Off / 15 min. / 30 min. / 45 min. / 60 min.           Teletext         Support           Power Supply         AC 100-240 V, 1.2A, 50/60Hz           Power Consumption         < 48W           Safety / EMC         TUV-GS, CE           Accessories	Screen Size	410.4(H) x 256.5(V)
Brightness 300 cd/m2  Contrast Ratio (typ.) 800 : 1  Response Time (typ.) 5 ms  Viewing Angles (typ.) 170°(H) / 160°(V)  Standard TV B/G, D/K, I, L/L=  Tuner System PAL, SECAM  Display Color 16.7 M  Control Panel Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR Receiver  Terminal I/O SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing 480i, 480p, 576i, 576p  User Controls Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption < 48W  Safety / EMC TUV-GS, CE  Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Aspect Ratio	16:10
Contrast Ratio (typ.) 800 : 1  Response Time (typ.) 5 ms  Viewing Angles (typ.) 170°(H) / 160°(V)  Standard TV B/G, D/K, I, L/L=  Tuner System PAL, SECAM  Display Color 16.7 M  Control Panel Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR Receiver  Terminal I/O SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing 480i, 480p, 576i, 576p  User Controls Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption < 48W  Safety / EMC TUV-GS, CE  Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Pixel Pitch	0.285(H) x 0.285(V)mm
Response Time (typ.) 5 ms  Viewing Angles (typ.) 170°(H) / 160°(V)  Standard TV B/G, D/K, I, L/L=  Tuner System PAL, SECAM  Display Color 16.7 M  Control Panel Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR Receiver  Terminal I/O SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing 480i, 480p, 576i, 576p  User Controls Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption < 48W  Safety / EMC TUV-GS, CE  Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Panel Resolution	1440 x 900
Response Time (typ.)5 msViewing Angles (typ.)170°(H) / 160°(V)Standard TVB/G, D/K, I, L/L=Tuner SystemPAL, SECAMDisplay Color16.7 MControl PanelPower (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR ReceiverTerminal I/OSCART x 2, TV Tuner, S-Video, CVBS, D-SubSupport Timing480i, 480p, 576i, 576pUser ControlsContrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)Pic-ModePersonal / Native / Soft / BrightSleep Timer FunctionOff / 15 min. / 30 min. / 45 min. / 60 min.TeletextSupportPower SupplyAC 100-240 V, 1.2A, 50/60HzPower Consumption< 48W	Brightness	300 cd/m2
Viewing Angles (typ.)170°(H) / 160°(V)Standard TVB/G, D/K, I, L/L=Tuner SystemPAL, SECAMDisplay Color16.7 MControl PanelPower (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR ReceiverTerminal I/OSCART x 2, TV Tuner, S-Video, CVBS, D-SubSupport Timing480i, 480p, 576i, 576pUser ControlsContrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)Pic-ModePersonal / Native / Soft / BrightSleep Timer FunctionOff / 15 min. / 30 min. / 45 min. / 60 min.TeletextSupportPower SupplyAC 100-240 V, 1.2A, 50/60HzPower Consumption< 48WSafety / EMCTUV-GS, CEAccessoriesRemote Control, Batteries, User Manual, Power Cord, Power AdapterVESA mounting75 x 75 mmSystem Dimension508(W) x 411(H) x 177(T) mmN.W.7 kg	Contrast Ratio (typ.)	800:1
Standard TVB/G, D/K, I, L/L=Tuner SystemPAL, SECAMDisplay Color16.7 MControl PanelPower (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR ReceiverTerminal I/OSCART x 2, TV Tuner, S-Video, CVBS, D-SubSupport Timing480i, 480p, 576i, 576pUser ControlsContrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)Pic-ModePersonal / Native / Soft / BrightSleep Timer FunctionOff / 15 min. / 30 min. / 45 min. / 60 min.TeletextSupportPower SupplyAC 100-240 V, 1.2A, 50/60HzPower Consumption< 48W	Response Time (typ.)	5 ms
Tuner System PAL, SECAM  Display Color 16.7 M  Control Panel Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR Receiver  Terminal I/O SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing 480i, 480p, 576i, 576p User Controls Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption < 48W  Safety / EMC TUV-GS, CE  Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Viewing Angles (typ.)	170°(H) / 160°(V)
Display Color  Control Panel  Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR Receiver  Terminal I/O  SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing  480i, 480p, 576i, 576p  User Controls  Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode  Personal / Native / Soft / Bright  Sleep Timer Function  Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext  Support  Power Supply  AC 100-240 V, 1.2A, 50/60Hz  Power Consumption  < 48W  Safety / EMC  TUV-GS, CE  Accessories  Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting  75 x 75 mm  System Dimension  508(W) x 411(H) x 177(T) mm  N.W.  7 kg	Standard TV	B/G, D/K, I, L/L=
Control Panel Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2), Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR Receiver  Terminal I/O SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing 480i, 480p, 576i, 576p User Controls Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz Power Consumption < 48W  Safety / EMC TUV-GS, CE Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Tuner System	PAL, SECAM
Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel IR Receiver  Terminal I/O SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing 480i, 480p, 576i, 576p  User Controls Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption < 48W  Safety / EMC TUV-GS, CE  Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Display Color	16.7 M
Terminal I/O  SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing  480i, 480p, 576i, 576p  User Controls  Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode  Personal / Native / Soft / Bright  Sleep Timer Function  Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext  Support  Power Supply  AC 100-240 V, 1.2A, 50/60Hz  Power Consumption  < 48W  Safety / EMC  TUV-GS, CE  Accessories  Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting  75 x 75 mm  System Dimension  508(W) x 411(H) x 177(T) mm  N.W.  7 kg	Control Panel	Power (On/Off), Source Select (TV/AV/S-Video/PC/SCART 1/SCART 2),
Terminal I/O  SCART x 2, TV Tuner, S-Video, CVBS, D-Sub  Support Timing  480i, 480p, 576i, 576p  User Controls  Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode  Personal / Native / Soft / Bright  Sleep Timer Function  Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext  Support  Power Supply  AC 100-240 V, 1.2A, 50/60Hz  Power Consumption  < 48W  Safety / EMC  TUV-GS, CE  Accessories  Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting  75 x 75 mm  System Dimension  508(W) x 411(H) x 177(T) mm  N.W.  7 kg		Menu (OSD) Operation, Volume +, Volume -, Channel Up, Channel
Support Timing480i, 480p, 576i, 576pUser ControlsContrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)Pic-ModePersonal / Native / Soft / BrightSleep Timer FunctionOff / 15 min. / 30 min. / 45 min. / 60 min.TeletextSupportPower SupplyAC 100-240 V, 1.2A, 50/60HzPower Consumption< 48WSafety / EMCTUV-GS, CEAccessoriesRemote Control, Batteries, User Manual, Power Cord, Power AdapterVESA mounting75 x 75 mmSystem Dimension508(W) x 411(H) x 177(T) mmN.W.7 kg		IR Receiver
User Controls  Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble, Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption Safety / EMC TUV-GS, CE Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Terminal I/O	SCART x 2, TV Tuner, S-Video, CVBS, D-Sub
Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)  Pic-Mode Personal / Native / Soft / Bright  Sleep Timer Function Off / 15 min. / 30 min. / 45 min. / 60 min.  Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption < 48W  Safety / EMC TUV-GS, CE  Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Support Timing	480i, 480p, 576i, 576p
Pic-ModePersonal / Native / Soft / BrightSleep Timer FunctionOff / 15 min. / 30 min. / 45 min. / 60 min.TeletextSupportPower SupplyAC 100-240 V, 1.2A, 50/60HzPower Consumption< 48W	User Controls	Contrast, Brightness, Hue, Saturation, Sharpness, Tone, Bass, Treble,
Sleep Timer FunctionOff / 15 min. / 30 min. / 45 min. / 60 min.TeletextSupportPower SupplyAC 100-240 V, 1.2A, 50/60HzPower Consumption< 48W		Balance, Sound Mode (News, Theater, Hall, Personal, Stereo)
Teletext Support  Power Supply AC 100-240 V, 1.2A, 50/60Hz  Power Consumption < 48W  Safety / EMC TUV-GS, CE  Accessories Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting 75 x 75 mm  System Dimension 508(W) x 411(H) x 177(T) mm  N.W. 7 kg	Pic-Mode	Personal / Native / Soft / Bright
Power Supply  AC 100-240 V, 1.2A, 50/60Hz  Power Consumption  48W Safety / EMC  TUV-GS, CE  Accessories  Remote Control, Batteries, User Manual, Power Cord, Power Adapter  VESA mounting  75 x 75 mm  System Dimension  508(W) x 411(H) x 177(T) mm  N.W.  7 kg	Sleep Timer Function	Off / 15 min. / 30 min. / 45 min. / 60 min.
Power Consumption< 48WSafety / EMCTUV-GS, CEAccessoriesRemote Control, Batteries, User Manual, Power Cord, Power AdapterVESA mounting75 x 75 mmSystem Dimension508(W) x 411(H) x 177(T) mmN.W.7 kg	Teletext	Support
Safety / EMCTUV-GS, CEAccessoriesRemote Control, Batteries, User Manual, Power Cord, Power AdapterVESA mounting75 x 75 mmSystem Dimension508(W) x 411(H) x 177(T) mmN.W.7 kg	Power Supply	AC 100-240 V, 1.2A, 50/60Hz
AccessoriesRemote Control, Batteries, User Manual, Power Cord, Power AdapterVESA mounting75 x 75 mmSystem Dimension508(W) x 411(H) x 177(T) mmN.W.7 kg	<b>Power Consumption</b>	< 48W
VESA mounting         75 x 75 mm           System Dimension         508(W) x 411(H) x 177(T) mm           N.W.         7 kg	Safety / EMC	TUV-GS, CE
System Dimension         508(W) x 411(H) x 177(T) mm           N.W.         7 kg	Accessories	Remote Control, Batteries, User Manual, Power Cord, Power Adapter
<b>N.W.</b> 7 kg	VESA mounting	75 x 75 mm
	System Dimension	508(W) x 411(H) x 177(T) mm
Speaker 3W x 2	N.W.	7 kg
	Speaker	3W x 2











...experience the future